


Certificate of Product Approval

Certificate Number: 010ba lssue: 04



36 Brookside Road Havant Hampshire PO9 1JR United Kingdom



Products

Visual Warning Devices

55000-740 55000-073

55000-741

55000-742

55000-743

55000-744

55000-745

55000-070

55000-071

55000-072

(refer to Appendix for details)

Standards

EN 54-23:2010

This Certificate is maintained and held in force through regular surveillance activities and subject to the corresponding ISO 9001 Certificate being maintained.

Signed for BRE Global Ltd

P Halligan

06 June 2017

08 January 2015

Date of First Issue





This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).

To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX

T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: enquiries@breglobal.com LPCB is a Registered Trademark of the Building Research Establishment Ltd.







Apollo Fire Detectors Limited

Certified Product	Description	LPCB Ref.No.
55000-740	Loop-Powered Type A VAD 15m (Red) Notes: 1. The ceiling mounted VAD meets the requirements of EN 54-23:2010 for the following: - Category rating C-3-15 - Synchronization - Flash rate 0.5 Hz - White LED - Clear lens 2. Approved with XP95/Discovery 45681-210 mounting base and 45681-284 short circuit isolating base	010ba/01
55000-741	Loop-Powered Type A VAD 7m (Red) Notes: 1. The wall mounted VAD meets the requirements of EN 54-23:2010 for the following: - Category rating W-2.4-6 - Synchronization - Flash rate 0.5 Hz - White LED - Clear lens 2. Approved with XP95/Discovery 45681-210 mounting base and 45681-284 short circuit isolating base	010ba/02
55000-742	Loop-Powered Type A VAD 8.5m (Red) Notes: 1. The ceiling mounted VAD meets the requirements of EN 54-23:2010 for the following: - Category rating C-3-8.5 - Synchronization	010ba/03

This Certificate is maintained and held in force through regular surveillance activities and subject to the corresponding ISO 9001 Certificate being maintained.

P Halligan

06 June 2017

08 January 2015

Signed for BRE Global Ltd

Date of Issue

Date of First Issue





This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).

To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX

T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: enquiries@breglobal.com LPCB is a Registered Trademark of the Building Research Establishment Ltd.







Apollo Fire Detectors Limited

Certified Product	Description	LPCB Ref.No.
	 Flash rate 0.5 Hz White LED Clear lens Approved with XP95/Discovery 45681-210 mounting base and 45681-284 short circuit isolating base 	
55000-743	Loop-Powered Type A VAD 15m (White) Notes: 1. The ceiling mounted VAD meets the requirements of EN 54-23:2010 for the following: - Category rating C-3-15 - Synchronization - Flash rate 0.5 Hz - White LED - Clear lens 2. Approved with XP95/Discovery 45681-210 mounting base and 45681-284 short circuit isolating base	010ba/04
55000-744	Loop-Powered Type A VAD 7m (White) Notes: 1. The wall mounted VAD meets the requirements of EN 54-23:2010 for the following: - Category rating W-2.4-6 - Synchronization - Flash rate 0.5 Hz - White LED - Clear lens 2. Approved with XP95/Discovery 45681-210 mounting base and 45681-284 short circuit isolating base	010ba/05

This Certificate is maintained and held in force through regular surveillance activities and subject to the corresponding ISO 9001 Certificate being maintained.

J. Malligan.
Signed for BRE Global Ltd

P Halligan

06 June 2017

08 January 2015

Date of Issue Date of First Issue





This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).

To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX

T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: enquiries@breglobal.com LPCB is a Registered Trademark of the Building Research Establishment Ltd.







Apollo Fire Detectors Limited

Certified Product	Description	LPCB Ref.No.
55000-745	 Loop-Powered Type A VAD 8.5m (White) 1. The ceiling mounted VAD meets the requirements of EN 54-23:2010 for the following: Category rating C-3-8.5 Synchronization Flash rate 0.5 Hz White LED Clear lens 2. Approved with XP95/Discovery 45681-210 mounting base and 45681-284 short circuit isolating base 	010ba/06
55000-070	 XP95 VAD C-3-15 (White Flash) (45681-518 base) Notes: Approved for Type B Outdoor use The ceiling mounted VAD meets the requirements of EN 54-23:2010 for the following: Synchronization Flash rate 0.5 Hz, 1 Hz Category setting: C-3-15 	010ba/07
55000-071	 XP95 VAD C-3-9 (Red Flash) (45681-518 base) Notes: Approved for Type B Outdoor use The ceiling mounted VAD meets the requirements of EN 54-23:2010 for the following: Synchronization Flash rate 0.5 Hz, 1 Hz Category setting: C-3-9 	010ba/08

This Certificate is maintained and held in force through regular surveillance activities and subject to the corresponding ISO 9001 Certificate being maintained.

P Halligan

06 June 2017

08 January 2015

Signed for BRE Global Ltd

Date of Issue

Date of First Issue





This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).

To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX

T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: enquiries@breglobal.com LPCB is a Registered Trademark of the Building Research Establishment Ltd.







Apollo Fire Detectors Limited

Certified Product	Description	LPCB Ref.No.
55000-072	XP95 VAD W-3.1-11.3 (White Flash) (45681-518 base) Notes: 1. Approved for Type B Outdoor use 2. The wall mounted VAD meets the requirements of EN 54-23:2010 for the following: - Synchronization - Flash rate 0.5 Hz, 1 Hz - Category setting: W-3.1-11.3	010ba/09
55000-073	XP95 VAD W-2.4-7.49 (Red Flash) (45681-518 base) Notes: 1. Approved for Type B Outdoor use 2. The wall mounted VAD meets the requirements of EN 54-23:2010 for the following: - Synchronization - Flash rate 0.5 Hz, 1 Hz - Category setting: W-2.4-7.49	010ba/10

Bases

45681-210 XP95/Discovery mounting base 45681-284 XP95/Discovery short circuit isolating base 45681-518 Enhanced Deep Isolating Base (Red)

This Certificate is maintained and held in force through regular surveillance activities and subject to the corresponding ISO 9001 Certificate being maintained.

f. Malligar.
Signed for BRE Global Ltd

P Halligan

06 June 2017

08 January 2015

Date of Issue Date of First Issue





This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).

To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX

T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: <u>enquiries@breglobal.com</u> LPCB is a Registered Trademark of the Building Research Establishment Ltd.



