



UL Product iQ
 UL'S NEXT GENERATION CERTIFICATIONS SEARCH
 The same trusted data in a modern search engine.

NOW AVAILABLE
 > **LEARN MORE**

UQGS.S5053
Heat-automatic Fire Detectors

Page Bottom

Heat-automatic Fire Detectors

See [General Information for Heat-automatic Fire Detectors](#)

APOLLO FIRE DETECTORS LTD
 36 BROOKSIDE RD
 HAVANT, HAMPSHIRE P09 1JR UNITED KINGDOM

S5053

Model No.	Type	Compatibility Restrictions	Contact Arrangement	Temp Range (°F)	Spacing (Ft)	
					Smooth Ceiling	to Wall or Partition
55000-138, 55000-139, 55000-140						
	FT/ROR	D2	-	135	50	25
55000-141, 55000-142, 55000-143						
	FT/ROR	D2	-	170	50	25
55000-144, 55000-145, 55000-146						
	FT/ROR	D2	-	200	50	25
55000-150	FT	D2	-	115	70	35
55000-151	FT/ROR	D2	-	160	50	25
55000-152	FT/ROR	D2	-	210	50	25
55000-153	FT	D2	-	135	50	25
55000-450 (a), 55000-451USM (a)						
	FT/ROR	D2	-	131-194	60	25
58000-450, 58000-451USM						
	FT/ROR	*1	-	135 (m1)	70	35
				150 (m2 / m3)	70	35
				200 (m4 / m5)	70	35
58000-750 (1), 58000-751USM (1)						
	FT	D2	-	135	70	35

Base Model	Related Detector	Control Unit Compatibility Restrictions
45681-200, 45681-220, 45681-232, 45681-251		
	55000-138, 55000-139, 55000-140, 55000-141, 55000-142, 55000-143, 55000-144, 55000-145, 55000-146, 55000-150, 55000-151, 55000-152, 55000-153	#1
45681-210, 45681-225, 45681-234		
	55000-450, 57000-400, 57000-401, 58000-450	#1
45681-227, 45681-230 45681-231, 45681-252		
	55000-150, 55000-151, 55000-152, 55000-153	#1
45681-242, 45681-250	55000-450, 58000-450	#1
45681-255, 45681-256, 45681-257, 45681-258		
	55000-138, 55000-139, 55000-140, 55000-141, 55000-142, 55000-143, 55000-144, 55000-145, 55000-146	#1

D2 - For connection to Listed control units with which compatibility was determined by test or a review of circuit parameters. Interconnection and compatible models indicated on installation wiring diagram for detector (base) and/or control unit.

#1 - For connection to Listed Control units Models ZXa and ZXe, manufactured by Morley IAS, employing software revision greater than 684aU0.

*1 - For connection to Listed Control units Models ZXa and ZXe, manufactured by Morley IAS, employing software revision greater than 684aU0.

FT/ROR - Fixed temperature/rate of rise combination

FT - Fixed temperature

(1) - Complementary Listed under Smoke-Automatic Fire Detectors (UROX)

(a) - Suitable for use in ambient temperatures of 0-66 C (32-150 F).

Last Updated on 2017-11-17

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".